

# **Smartet Technology Development Co., Ltd** SuHua Medical Material Manufacture Co.,Ltd

Building1,No1,North YongXing Road,YongXing Industrial Park,HengLan Town, ZhongShan City GuangDong China Tel:0086-760-88873088 Fax:0086-760-88873008 E-mail: ivan@smartet.net web:www.perfwipe.com

# PERFWIPE ESD PC Polyester Cleanroom wiper Specification

#### **Product Description:**

Perfwipe ESD PC polyester cleanroom wiper are made with 100% continuous-filament 85 denier standard medium-weight polyester with conductive fiber designed to dissipate electrical charge. A double knite interlock, no-run circular pattern.

Contains conductive carbon fiber designed to dissipate electrical charge.

Laser Sealed Border for maximum fiber& particl retention.

These wiper are packed in a static shield bag.

Laundered and package in a controlled environment.

Lot control quality tested.

#### Composition&Attributes:

100% continuous-filament 85 denier standard medium-weight polyester with conductive fiber Contains conductive carbon fiber designed to dissipate electrical charge.

Laser Border Sealed Edges for maximum fiber & particle retention

Solvent safe double bag cleanroom packaging

Resists abrasion when used with rough surfaces

Works well with IPA and other cleaning solvents

# **Applications:**

Ideal for wiping critical surfaces to achieve ultra cleanliness Excellent choice for wiping process tool internals and chambers Works well for particle removal & resistance with solvents Soft texture for scratch sensitive surfaces but very durable **Autoclavable for Aseptic environments** Compatible with ISO Class 4-5(Class 10-100) environments

# **Physical Properties:**

Basis Weight: 115g/m2

Material:

- Polyester & Carbon Fiber

- Continous Filament, Double Knit

Absorbency:

- Sorptive Capacity: 360 mL/m2 - Sorptive Rate: < 1.3seconds

Test Method: IEST-RP-CC004.3 Section 8.1



# Smartet Technology Development Co.,Ltd SuHua Medical Material Manufacture Co.,Ltd

Building1,No1,North YongXing Road,YongXing Industrial Park,HengLan Town, ZhongShan City GuangDong China Tel:0086-760-88873088 Fax:0086-760-88873008 E-mail: ivan@smartet.net web:www.perfwipe.com

### **Purity Specifications:**

#### Particles & Fibers:

- Particles:
  - $(>0.5 micron) = 3.0 \times 10(6) particles/m2$
  - (> 5 micron) = 0.2x10(6)particles/m2
- Fibers:
  - (>100 micron)=200/m2

Test Method:Orbital Shake Test:- IEST-RP-CC004.3-6.1.4

Nonvolatile Residue:

- IPA Extractant: 1.5 ug/cm2- DIW Extractant: 0.90ug/cm2

Test Method:Short Term Extraction:- IEST-RP-CC004.3-7.1.2

**Extractable lons:** 

-Sodium (Na+): 0.20ug/g
-Potassium (K+): 0.09ug/g
-Chloride (Cl+): 0.07ug/g

Test Method: Standard Extractable Method: - IEST-RP-CC004.3-7.2.2.1B

ESD Specifications Upper Limits Test Method Surface Resistivity 10x10(6~9)ohms EOS/ESD S11.11

Decay Time 1.3 seconds FTM STD 101-Method 4046

#### **Order Informations:**

Code	Size	Packaging
SSESDW-PC-LE-115D-44	4"x4"	600pcs/bag 10bag/case
SSESDW-PC-LE-115D-66	6"x6"	150pcs/bag 20bag/case
SSESDW-PC-LE-115D-99	9"x9"	150pcs/bag 10bag/case
SSESDW-PC-LE-115D-1212	12"x12"	100pcs/bag 10bag/case

Note: The data in this table represent typical analyses of these wipers at the time of publication. These are not specifications.

Smartet continually refines both its processes and its products.

(End